

TERMORESISTENZA PT100 AD ISOLAMENTO MINERALE (MgO) CON CAVO USCENTE PT100 THERMAL RESISTANCE WITH MINERAL- INSULATION (MgO) AND OUTLET CABLE

**TOLLERANZA ELEMENTO SENSIBILE (IEC 751)
SENSIBLE ELEMENT ACCURACY (IEC 751)**

Classe "B" ($\pm 0.3^{\circ}\text{C}$ a 0°C)	0
Classe "A" ($\pm 0.15^{\circ}\text{C}$ a 0°C)	3

**CAVO USCENTE
EXPIRING CABLE**

PVC TERMOELEMENTI ISOLATI IN PVC + GUAINA IN PVC (-30/+80°C) INSULATED THERMOELEMENTS IN PVC + PVC SHEATH (-30/+80°C)	1
GS TERMOELEMENTI ISOLATI IN GOMMA SILICONATA + GUAINA IN GOMMA SILICONATA (-60/+200°C) INSULATED THERMOELEMENTS IN SILICONED RUBBER + SHEATH IN SILICONED RUBBER (-60/+200°C)	2
GSS TERMOELEMENTI ISOLATI IN GOMMA SILICONATA + GUAINA IN GOMMA SILICONATA + GUAINA CON FILI DI RAME STAGNATO (-60/+200°C) INSULATED THERMOELEMENTS IN SILICONED RUBBER + SHEATH IN SILICONED RUBBER + SHEATH WITH TINNED COPPER WIRE (-60/+200°C)	3
TTS TERMOELEMENTI ISOLATI IN FIBRA DI VETRO SILICONATO + CALZA IN FIBRA DI VETRO + GUAINA CON FILI DI RAME STAGNATO (-60/+250°C) INSULATED THERMOELEMENTS IN SILICONED FIBRE GLASS + BRAIDED WIRE IN FIBRE GLASS + SHEATH WITH TINNED COPPER WIRE (-60/+250°C)	4
FTS TERMOELEMENTI ISOLATI IN MFA + SCHERMATURA A TRECCIA + MFA (-60 / + 250°C) INSULATED THERMOELEMENTS IN MFA + COPPER PLAIT SHIELD + MFA (-60 / + 250°C).	5

**DIAMETRO GUAINA
SHEATH DIAMETER**

	ϕA	ϕB
30	3 mm.	(6)
45	4.5 mm.	(6)
60	6 mm.	(8)

**LUNGHEZZA (L1)
LENGTH (L1)**

	L1 = mm.
01	85 mm.
02	135 mm.
03	185 mm.
04	235 mm.
05	285 mm.
06	335 mm.
07	385 mm.
08	435 mm.
09	485 mm.
10	535 mm.
11	585 mm.
12	635 mm.
13	685 mm.
14	735 mm.
15	785 mm.
16	835 mm.
17	885 mm.
18	935 mm.
19	985 mm.
20	1035 mm.
22	1135 mm.
24	1235 mm.
26	1335 mm.
28	1435 mm.
30	1535 mm.
32	1635 mm.
34	1735 mm.
36	1835 mm.
38	1935 mm.
40	2035 mm.
42	2135 mm.
44	2235 mm.
46	2335 mm.
48	2435 mm.
50	2535 mm.
52	2635 mm.
54	2735 mm.
56	2835 mm.
58	2935 mm.
60	3035 mm.

Cod.

3	4	5		.	7		1	.				
---	---	---	--	---	---	--	---	---	--	--	--	--

* LUNGHEZZE DIVERSE DA MT. 3 SONO DISPONIBILI A RICHIESTA
DIFFERENT LENGTHS FROM 3 MT. AVAILABLE ON REQUEST

LIMITI DI TEMPERATURA -70°C / +500°C
TEMPERATURE LIMITS

IMMERSIONE MINIMA 40 MM.
MINIMUM IMMERSION 40 MM.

